

## Turntable TT 1.2 WI

### Technical Data

Diameter		1.2 m
Permissible load		500 kg
Point load		125 kg (at area of 10cm x 10cm)
Height up to ferrite cover	min.	118 mm
Total height	min.	166 mm
Material carrier plate		Laminated wood
Rotating speed adjustable between		0.3 to 2.5 rpm
Rotating angle		+400°/-200°
Positioning accuracy		+/- 0.5°
Motor		Brushless DC motor 200 W
Interference suppression:		20 dB under limits EN 55022 class B
Turntable drive		Toothed belt drive, worm gear
Control cable		Fibre optic lines
Remote control via		IEEE interface
Current consumption	max.	2 A
Voltage		208-230 VAC, 50/60 Hz, single phase
Temperature range		+10°C to +35°C
Total weight	approx.	120 kg
Accessories		Interface to SCU/MCU/NCD Controller 1.5 m power supply cable Service manual

### Brief description


The turntable **TT 1.2 WI** is especially designed for installation in fully anechoic electromagnetic absorption chambers. The carrier plate is made of waterproof, laminated and lacquered wood.

There is a division plate between the wooden plates, which can be covered with ferrite tiles in order that there are no metal parts above the ground plane.

A 285 mm diameter opening in the centre of the turntable provides the capability to insert power supply for testing.

The **IEEE 488.2 (GPIB) bus** provides an additional control option for all functions, when operated with the **SCU/MCU or NCD Controller**.

## Turntable TT 1.2 WI



Information presented enclosed is subject to change as product enhancements are made regularly. Pictures included are for illustration purposes only and do not represent all possible configurations.